



Compact-type Shrink Tunnel

小型シュリンクトンネル TD-32007・TD-42507・TD-52509 etc.



*Photo: TD-32007/TD-42507/TD-52509

汎用性が高く さまざまな業界の小物商品のシュリンク包装に適しています
ロット生産により低価格販売を実現し 多くの納入実績を誇ります

Owing to its versatility, our Compact-type Shrink Tunnels are suited for packaging small products regardless of your industries.

We have successfully introduced so many Tunnels at low price by lot production.



長寿命で熱効率に優れたフィンヒーターを搭載
省資源で環境にやさしい 安心のラインナップからおえらびください

Long-life and high heat-efficient fin heater is equipped with these Tunnels.
You can find the best one among our Tunnels which are resource saving and eco-friendly.

● 特徴 Features

- コンパクトな操作パネルで シンプルな構造
 - 商品に合わせて 温度・熱風量・速度などの調整が容易
 - L型包装機との接続も可能
- Our Tunnels have simple structure with compact operator panel.
 - It is easy to adjust chamber temperature, heat air volume and conveyor speed for each product.
 - L-type Sealing Machine can be integrated with these Tunnels.

● 仕様 Specifications

機種名 Model	TD-32007	TD-42507	TD-52509 (TD-53509)	TD-62509 (TD-63509)
トンネル内有効寸法 Dimensions of inside of chamber	W290 × H190 × L700mm	W310 × H230 × L700mm	W420 × H225 × L900mm (W420 × H330 × L900mm)	W520 × H225 × L900mm (W520 × H330 × L900mm)
機械寸法 Machine dimensions	W550 × H1290 × L1100mm * In case of floor level 745mm	W650 × H1290 × L1100mm * In case of floor level 700mm	W700 × H1370 × L1200mm * In case of floor level 700mm (W700 × H1460 × L1200mm * In case of floor level 695mm)	W800 × H1470 × L1200mm * In case of floor level 750mm (W800 × H1550 × L1200mm * In case of floor level 750mm)
コンベヤスピード Conveyor speed	Approx. 5.7~14.0m/min.	Approx. 10.0~24.0m/min.	Approx. 7.2~14.5m/min.	Approx. 7.0~14.0m/min.
トンネル内温度 Chamber temperature	50 ~ 200°C	50 ~ 200°C	50 ~ 200°C	50 ~ 200°C
電源 Main power	3 φ, 200V AC, 50/60Hz, 15A, 4.5kW (heater 3.6kW)	3 φ, 200V AC, 50/60Hz, 30A, 7.0kW (heater 6.3kW)	3 φ, 200V AC, 50/60Hz, 30A, 8.0kW (heater 6.3kW)	3 φ, 200V AC, 50/60Hz, 30A, 9.0kW (7.2kW)

※掲載以外の仕様についてはお問い合わせください Please inquire about other specifications if necessary.

 **株式会社ニッサンキコー**
NISSAN KIKO CO.,LTD.

Web site/ <http://www.nissankiko.co.jp>



Fun to Share
みんなでシェアして、低炭素社会へ。

- 本 社/〒611-0041 京都府宇治市槇島町吹前107番地
TEL.0774-22-1115 FAX.0774-20-5250
- 東京支店/〒110-0016 東京都台東区台東1丁目24番1号
燦坤日本電器ビル1階
TEL.03-3837-8380 FAX.03-3837-8360
- Main Office/107 Fukimae, Makishima-cho, Uji City, Kyoto, 611-0041, Japan
TEL. +81-774-22-1115 FAX. +81-774-20-5250
- Tokyo Office/TSANN KUEN BLDG. 1F, 1-24-1,
Taito, Taito-ku, Tokyo, 110-0016, Japan
TEL.+81-3-3837-8380 FAX.+81-3-3837-8360