



Compact-type Shrink Tunnel

小型シュリンクトンネル TD-32007・TD-42507・TD-52509 etc.



*Photo: TD-32007/TD-42507/TD-52509

汎用性が高く さまざまな業界の小物商品のシュリンク包装に適しています
ロット生産により低価格販売を実現し 多くの納入実績を誇ります

Owing to its versatility, our Compact-type Shrink Tunnels are suited for packaging small products regardless of your industries.

We have successfully introduced so many Tunnels at low price by lot production.



株式会社ニッサンキコー



長寿命で熱効率に優れたフィンヒーターを搭載
省資源で環境にやさしい 安心のラインナップからおえらびください

Long-life and high heat-efficient fin heater is equipped with these Tunnels.
You can find the best one among our Tunnels which are resource saving and eco-friendly.

● 特徴 Features

- コンパクトな操作パネルで シンプルな構造
- 商品に合わせて 温度・熱風量・速度などの調整が容易
- L型包装機との接続も可能
- Our Tunnels have simple structure with compact operator panel.
- It is easy to adjust chamber temperature, heat air volume and conveyor speed for each product.
- L-type Sealing Machine can be integrated with these Tunnels.

● 仕様 Specifications

機種名 Model	TD-32007	TD-42507	TD-52509 (TD-53509)	TD-62509 (TD-63509)
トンネル内有効寸法 Dimensions of inside of chamber	W290 × H190 × L700mm	W310 × H230 × L700mm	W420 × H225 × L900mm (W420 × H330 × L900mm)	W520 × H225 × L900mm (W520 × H330 × L900mm)
機械寸法 Machine dimensions	W550 × H1290 × L1100mm * In case of floor level 745mm	W650 × H1290 × L1100mm * In case of floor level 700mm	W700 × H1370 × L1200mm * In case of floor level 700mm (W700 × H1460 × L1200mm * In case of floor level 695mm)	W800 × H1470 × L1200mm * In case of floor level 750mm (W800 × H1550 × L1200mm * In case of floor level 750mm)
コンベヤスピード Conveyor speed	Approx. 5.7~14.0m/min.	Approx. 10.0~24.0m/min.	Approx. 7.2~14.5m/min.	Approx. 7.0~14.0m/min.
トンネル内温度 Chamber temperature	50 ~ 200°C	50 ~ 200°C	50 ~ 200°C	50 ~ 200°C
電源 Main power	3 φ, 200V AC, 50/60Hz, 15A, 4.5kW (heater 3.6kW)	3 φ, 200V AC, 50/60Hz, 30A, 7.0kW (heater 6.3kW)	3 φ, 200V AC, 50/60Hz, 30A, 8.0kW (heater 6.3kW)	3 φ, 200V AC, 50/60Hz, 30A, 9.0kW (7.2kW)

※掲載以外の仕様についてはお問い合わせください Please inquire about other specifications if necessary.

 **株式会社ニッサンキコー**
NISSAN KIKO CO.,LTD.

Web site/ <http://www.nissankiko.co.jp>



Fun to Share
みんなでシェアして、低炭素社会へ。

- 本 社/〒612-8496 京都府京都市伏見区久我西出町1-11
TEL.075-950-1871 FAX.075-950-4391
- 東京支店/〒110-0016 東京都台東区台東1丁目24番1号
燦坤日本電器ビル1階
TEL.03-3837-8380 FAX.03-3837-8360

- Head Office/1-11, Koanishide-cho, Fushimi-ku, Kyoto, 612-8496, Japan
TEL. +81-75-950-1871 FAX. +81-75-950-4391
- Tokyo Office/TSANN KUEN BLDG. 1F, 1-24-1,
Taito, Taito-ku, Tokyo, 110-0016, Japan
TEL.+81-3-3837-8380 FAX.+81-3-3837-8360